


# LOGGING CRANES WITH THREE-POINT MOUNTING

**FOR PROFESSIONAL APPLICATION** | The crane employs modular construction techniques and is available in lengths of 1.9 m and 4.5 m. In addition, the crane can be combined with a variety of mounted equipment (scoop, drill, etc.). The cranes are available either with three-point or with quick-change mounting. All three-point mounting cranes can be combined with a RITTER mounted winch. The systems are controlled by the tractor's existing control unit or by a separate control unit with joystick.



**LIFTING POWER DK 4.5**  
Values are calculated at p = 200 bar  
Values without load suspension device

- 1.0 m extension 2570 kg
- 2.0 m extension 1440 kg
- 3.0 m extension 1100 kg
- 4.0 m extension 780 kg
- 4.5 m extension 700 kg

## LOGGING CRANE WITH THREE-POINT MOUNTING DK 1.9 / DK 4.5 TECHNICAL DATA AND PRICES

TYPE	DK 1.9	DK 4.5
Working radius (m)	1,9	4,5
Own weight (kg)	390	650
Weight grapple and rotator (kg)	120 bis 160	120 bis 160
For vehicles from...to... (kW/HP)	29/40 – 74/100	48/65 – 88/120
Telescope	Single	Single
Stump guard	–	Standard
Directional valves (electric switching)	3	4
<b>Base price Logging Crane swivel range: 100°</b>	<b>6.900.–</b>	<b>–</b>
<b>Base price Logging Crane swivel range: 160°</b>	<b>–</b>	<b>13.100.–</b>

All logging cranes with three-point mounting with cylinder swivelling mechanism.  
Three-Point Mounting: Category II/III. Oil supply: Tractor's hydraulics.  
Control units required on vehicle: 2.

ACCESSORIES / FREIGHT	DK 1.9 / DK 4.5
Logging grapple RHG 1100 Max. opening 1100 mm	(RHG 1100) <b>900.–</b>
Logging grapple RHG 1300 Max. opening 1300 mm	(RHG 1300) <b>1.200.–</b>
Endless rotator GR465/68M	<b>830.–</b>
Rotor hanger with brake	(BR10/7035) <b>170.–</b>
Set of hoses for rotator, Grapple completely assembled	(RK-01-10-09) <b>330.–</b>
Skidding blade 1500mm screwable	(DK-01-11-01) <b>330.–</b>
<b>BUCHER Crane control block</b> Joystick if no control units available in vehicle	(00-01-10-785) <b>3.500.–</b>
<b>BUCHER Multi-lever control unit</b> no directional valves	(HSVWAL 150003) <b>2.300.–</b>

All prices given in EURO, exclusive of VAT. Pricing basis Zell a.H.

Mounting on tractor's rail with skidding blade



DK 4.5 with scoop

DK 1.9 combined with mounted winch



Quick-change variation with skidding blade

DK 4.5 with Quick-change mounting



DK 4.5 with skidding grapple